



The Programme

on a view

Cutting system

Model FM 128 Table model	K 250	K 320	K 400	K 450	K 580
Tray- roller broad (mm)	250	320	400	450	580
Baking space abroad the tray	ca. 205	ca. 295	ca.370	ca. 405	ca.560
Standard capacity insquare meters per minute	ca. 1	ca. 1,3	ca. 1,6	ca. 1,8	ca. 2,3
Mains voltage (KW)	2,3	2,3	4,3	4,3	4,3
Measure of the table model when machine is working (mm)					
length	1250	1250	1450	1450	1450/2350
width	580	640	780	780	930
height	630	630	630	630	630
Measure of the cupboard (mm)					
length	1200	1200	1200	1200	1200
width	490	570	700	700	850
height	650	650	650	650	650
Measures of the open stand, long and short version (mm)					
length	590/1140	1140	900	900	900
width	490	570	700	700	850
height	640	640	645	645	645

Rubber roller suction belt system

Model FM 126 Table model	M 250	M 320	M 400	M 450	M 580
Tray- roller broad (mm)	250	320	400	450	580
Baking space abroad the tray	205	295	370	405	560
Standard capacity insquare meters per minute	ca. 1	ca. 1,3	ca. 1,6	ca. 1,8	ca. 2,3
Mains voltage (KW)	0,37	0,37	0,37	0,37	0,37
Measure of the table model when machine is working (mm)					
length	1200	1200	1370	1570	1570
width	570	650	770	770	920
height	550	550	570	570	570
Measure of the cupboard (mm)					
length	1200	1200	1200	1200	1200
width	490	570	700	700	850
height	650	650	650	650	650
Measures of the open stand, long and short version (mm)					
length	790/1140	1140	900	900	900
width	480	560	700	700	850
height	640	640	645	645	645

We reserve the right to change the machine specification datas without prior information
Issued 7/98